



britomatics engineers private limited

Resin Bonded Cartridges

Utility:

Cartridge for high fluid viscosity applications.

Description:

Britomatics resin bonded type cartridges are designed to have two-stage filtration process to maximise particle removal. The cartridge is suitable for viscous fluid filtration application as it has a longer service life. The spiral wound pre filter wrap ensures cartridge strength and eliminates residuals normally associated with resin bonded cartridges of conventional manufacture.

The cartridges are available in 2u, 5u, 10u, 25u, 50u and up to 150um pore sizes to meet wide performance level.

Features and benefits:

- Extra long acrylic fibers provide added strength and resist breakage and migration common with short fiber cartridges.
- Use of phenolic resin strengthens the cartridge for use with high fluid viscosity application.
- Cartridge is designed to withstand high pressure
- The cartridge is of single piece construction which helps ease change out.
- High filtration efficiency
- High dirt holding capacity
- Wide range of micron retention
- Faster flow rates
- Quality consistency
- Silicon-free construction prevents contamination to adversely affect adhesion properties of coating

Applications:

Paints, Varnishes, Lubricants, Printing Inks, Adhesives, Process Water, Emulsions, Solvents, Waxes, Plasticizers, Petroleum Products, Chemical Coatings.

CONTACT DETAILS

Britomatics Engineers Pvt. Ltd

A-285, M.I.D.C., T.T.C Industrial Area,
Shil Phata Road, Mahape,
Navi Mumbai 400 701,
Maharashtra, India

Tele.:-91-22-27781676,
27781677, 27781679,
Fax :- 91-22-27781682

For Queries:

britomatics@vsnl.com
britomatics@mtnl.net.in